

SIZE OF ACCESSORY BUILDING ___ x ___

TRUSSES: @ ___" o/c

RIDGE BOARD ___" x ___"

ROOF SHEATHING: _____

ROOF COVERING: _____

COLLAR TIES 2" x ___" @ ___ o/c

RAFTERS 2" x ___" @ ___ o/c

CEILING JOIST 2" x ___" @ ___ o/c

EAVESTROUGH

DOUBLE TOP PLATE 2" x ___"

WALL STUDS 2" x ___" @ ___ o/c

INSULATION: R ___

WALL SHEATHING: _____

EXTERIOR CLADDING: _____

BOTTOM PLATE BOLTED WITH 1/2"Φ ANCHOR BOLTS @ 7'-10" o/c MAX WITH SILL GASKET OR POLY TO SEPERATE WOOD FROM CONCRETE

SEE DRAWING NO. A-4

MIN 3" CONCRETE FLOOR SLAB AT 32 MPa, 5-8% AIR ENTRAINMENT

4" GRANULAR FILL (RECOMMENDED)

LINTEL ___ PLY 2" x ___"

WIDTH OF DOOR OPENING
___' - ___"

CONCRETE FOUNDATION: ___ MPa, ___" THICK

CONCRETE FOOTING ___" x ___"

OVERALL HEIGHT (16'-0" MAXIMUM FROM GRADE TO PEAK)

WALL HEIGHT

4'-0" MIN

12

NOTE: BUILDINGS LARGER THAN 592 SQ. FT. IN AREA MUST BE SUPPORTED BY FOOTINGS AND FOUNDATION WALL, UNLESS ENGINEERED.

TOWNSHIP OF WELLESLEY
BUILDING DEPARTMENT



4639 LOBSINGER LINE
RR#1 ST CLEMENTS, ON N0B 2M0
519-699-4611
FAX: 519-699-4540

DWG NO:
A-3