

SECTION 11 **URBAN RESIDENTIAL TWO (UR2) ZONE REGULATIONS**

The Urban Residential Two (UR2) Zone is intended to apply to residential lots within areas designated “Urban Residential” in the Wellesley Urban Area in the Official Plan.

11.1 PERMITTED USES

No land shall be used and no buildings or structures shall be erected, used, or altered in the Urban Residential Two (UR2) Zone except for the following purposes:

- Townhouse dwelling;
- Semi-detached dwelling;
- Triplex dwelling;
- Fourplex dwelling;
- Home occupation;
- Bed and Breakfast;
- Additional Detached Dwelling Unit;
- Additional Attached Dwelling Unit;
- Accessory uses to the above permitted uses.

11.2 MINIMUM LOT AREA

Semi-detached dwelling	275 m ²
Townhouse (per dwelling unit)	175 m ²
Triplex	750 m ²
Fourplex	850 m ²

11.3 MINIMUM LOT FRONTAGE

Semi-detached dwelling	18.0 m (interior lot)
	21.0 m (corner lot)
Townhouse	6.0 m (interior lot)
	12.0 m (corner lot)
Triplex	18.0 m
Fourplex	21.0 m

Residential Cluster Development, which shall be defined as: where multiple single detached dwellings, semi-detached dwellings, and/or townhouse dwellings are located on a lot to allow the remaining land to be used for a variety of open space and common element purposes;

Single detached dwellings;

Townhouse dwellings including cluster townhouse dwellings and street townhouse dwellings.

Minimum Lot Area

Single detached dwelling	510 m ²
Semi-detached dwelling	210 m ² per unit

Minimum Lot Frontage

Single detached dwelling	12 m
Semi-detached dwelling	9 m per unit (interior lot)
Townhouse dwelling	6 m per unit

Maximum Building Height

Semi-detached and Townhouse units 7.5 m

Notwithstanding any other provisions of this by-law to the contrary building height for the purposes of this development shall be measured along the front façade of the building.

Minimum Floor Area

Single detached dwelling	100 m ²
Semi-detached dwelling	80 m ²
Townhouse dwelling	80 m ²

Minimum Front Yard Depth

The existing single detached dwelling on the property municipally known as 1016 Doering Street shall have a minimum front yard depth of 3.0 m.

All other dwellings shall have a minimum front yard depth of 4.5 m for the dwelling and 6.0 m for a private garage. For corner lots/units and other lots/units adjoining a curved street, a minimum front yard depth of 3.0 m shall be required for the dwelling, but in no case shall the private driveway depth be less than 6.0 metres in depth.

Minimum Side Yard Width

The existing single detached dwelling on the property municipally known as 1018 Doering Street shall have a minimum interior side yard width of 1.2 m plus 0.5 m for each additional or partial storey above the first storey, and a minimum exterior side yard width of 2.5 m.

Semi-detached and townhouse dwellings shall have a minimum interior side yard width of 1.5 m where there is an exterior wall and 0.0 m where there is a common wall.

Semi-detached and townhouse dwellings shall have a minimum exterior side yard width of 3.0 m.

Minimum Rear Yard Depth

Semi-detached dwelling	6.0 m
Single detached dwelling	7.5 m
Townhouse dwelling	6.0 m

Maximum Lot Coverage

Single detached dwelling	50%
Semi-detached dwelling	45%
Townhouse dwelling	55%, except that a maximum of 10 lots/units may have a maximum lot coverage of up to 60% provided that an equal number of lots/units do not exceed a maximum lot coverage of 50%

Parking

Notwithstanding subsection 4.29.5 of this By-law, the lot coverage of required parking spaces shall not exceed twenty (20) percent of the total lot area.

Regulations for Cluster Development

For a cluster development, the required minimum yards shall be measured appurtenant to the buildings as follows:

- i. For any building that does not have frontage on a public street, the front yard depth shall be measured from the front wall of the building to the edge of the travelled portion of the adjoining private street, common driveway or common element road right-of-way;
- ii. For any building with an exterior side wall facing a private street, common driveway or common element road right-of-way, the minimum exterior side yard width shall be measured from said exterior side wall of the building to the edge of the travelled portion of the adjoining private street, common driveway or common element road right-of-way;
- iii. For any building with an exterior side wall adjoining an interior lot line, the minimum interior side yard shall be measured between the exterior side wall and the lot line;
- iv. For any building with an exterior side wall facing an exterior side wall of another building, the minimum setback between buildings shall be 3 m;
- v. For any building with an exterior side wall adjoining a lot line that does not adjoin any street or right-of-way, the minimum interior side yard shall be measured between the exterior side wall and the lot line;
- vi. For any building with an exterior rear wall adjoining an interior lot line, the minimum rear yard shall be measured between the exterior rear wall and the lot line;
- vii. For any building with an exterior rear wall facing any exterior wall of another building, the minimum setback between buildings shall be 7.5 m;

Notwithstanding anything to the contrary, for cluster development, more than one (1) building shall be permitted on a lot.

11.11.3

Defined Area

UR2-3 as shown on Schedule “B-4”, to this By-law

Added by By-law 28-20

Minimum Lot Area

738m²